

# THE BEAST

## PACKING DETAILS

Dimensions (mm)	Nominal Thickness (mm)	No. of Tiles / Box	Coverage Area
1200x2400	6	1	2.88 sq. m

## TECHNICAL SPECIFICATIONS

S.No.	Property	Standard Requirements	Our Value	Test according to
1.	Deviation in length & Width	± 0.6%	± 0.1%	UNI EN ISO 10545-2
2.	Deviation in Thickness	± 5%	± 5%	UNI EN ISO 10545-2
3.	Edge Straightness	± 0.5%	± 0.1%	UNI EN ISO 10545-2
4.	Rectangularity	± 0.6%	± 0.1%	UNI EN ISO 10545-2
5.	Surface Flatness	± 0.5%	± 0.15%	UNI EN ISO 10545-2
6.	Surface quality (%)	≥ 95%	Compliant	UNI EN ISO 10545-2
7.	Water absorption	≤ 0.5%	≤ 0.1%	UNI EN ISO 10545-3
8.	Bending Strength	≥ 35 N/mm <sup>2</sup>	50 N/mm <sup>2</sup>	UNI EN ISO 10545-4
9.	Frost Resistance	Resistant	Frost Proof	UNI EN ISO 10545-12
10.	Resistance to Thermal Shock	Resistant	Resistant	UNI EN ISO 10545-9
11.	Colour Resistance to Light Exposure	Resistant	Resistant	
12.	Chemical Resistance	UB Minimum	UA; ULA; UHA	UNI EN ISO 10545-13
13.	Stain Resistance	Class 3 Minimum	Matt Class-4, Others Class 5	UNI EN ISO 10545-14
14.	Resistance to Surface Abrasion	Manufacturer to State Abrasion class	PEI Class 3-5	UNI EN ISO 10545-7
15.	Deep Abrasion Resistance	≤ 175 mm <sup>3</sup>	≤ 145 mm <sup>3</sup>	UNI EN ISO 10545-6

- Colours in the catalogue are as accurate as printing process allows, Please check actual sample tiles before making final selection
- Sizes mentioned in the catalogue are the nominal sizes only
- For better laying please follow the instructions mentioned on the packaging box.
- No claim will be entertained once the tiles are fixed.
- It is advisable to use polymer based adhesive for fixing tiles.
- Shades may vary, depending upon batch wise production